

Report on Hydraulic Fracturing Fluid

The content of hydraulic fracturing fluid is adapted to the geological conditions of each well site. Hydraulic fracturing fluid is typically 98 - 99.5 per cent water and sand, with the remaining 0.5 - 2 per cent comprised of chemical additives that are needed to make the process more effective (e.g. reducing friction, preventing corrosion, inhibiting bacterial growth). Many of these substances are found in household products such as cosmetics, shampoo and cleaning products.

Hydraulic fracturing flowback and water produced during the process is increasingly being recycled by industry to minimize any potential environmental impacts and use of local water infrastructure.

Compound*	Purpose	Common application
Acids	Helps dissolve minerals and initiate fissure in rock (pre-fracture)	Swimming pool cleaner
Glutaraldehyde	Eliminates bacteria in the water	Disinfectant, Sterilizer for medical and dental equipment
Sodium Chloride	Allows a delayed break down of the gel polymer chains	Table Salt
N, n-Dimethyl formamide	Prevents the corrosion of the pipe	Used in pharmaceuticals, acrylic fibers and plastics
Borate salts	Maintains fluid viscosity as temperature increases	Used in laundry detergents, hand soaps and cosmetics
Polyacrylamide	Minimizes friction between fluid and pipe	Water treatment, soil conditioner
Petroleum distillates	"Slicks" the water to minimize friction	Make-up remover, laxatives, and candy
Guar gum	Thickens the water to suspend the sand	Thickener used in cosmetics, baked goods, ice cream, toothpaste, sauces, and salad dressing
Citric Acid	Prevents precipitation of metal oxides	Food additive, food and beverages, lemon juice
Potassium chloride	Creates a brine carrier fluid	Low sodium table salt substitute
Ammonium bisulfite	Removes oxygen from the water to protect the pipe from corrosion	Cosmetics, food and beverage processing, water treatment
Sodium or potassium carbonate	Maintains the effectiveness of other components, such as crosslinkers	Washing soda, detergents, soap, water softener, glass and ceramics
Proppant	Allows the fissures to remain open so the gas can escape	Drinking water filtration, play sand
Ethylene glycol	Prevents scale deposits in the pipe	Automotive antifreeze, household cleansers, deicing, and caulk
Isopropanol	Used to increase the viscosity of the fracture fluid	Glass cleaner, antiperspirant, and hair color